

CSK-960 Frame Adhesive

1. Product description

- One component, Ready-to-use.
- High water resistance, Resistance only to mild solvents for a short period.
- Can be used on all types of frames, including wood.
- Suitable for high tension stretching.
- Can be diluted for cleaning with toluene.
- Resists up to 60°C

2. Application

- Apply first one coat by brush onto the frame.
- Let dry.
- Stretch mesh.
- Apply second coat with squeegee or spatula and rub on well.
- Dry for 5 – 15 minutes depending on mesh number and room temperature .
- Wait a few minutes before opening the stretching device.
- The screen is ready for further processing.

3. Hints

- This product has a limited heat resistance. It is important that the stretched frames are not submitted to temperatures over 50°C in the drying cabinet or under ambient conditions.

4. Shelf-life

Under normal room conditions 8 – 12 months.
The can must be kept well closed.

5. Safety and health

- Use in well ventilated areas.
- Keep away from children.
- Consult the Material Safety Data Sheet.

For additional product information, please contact with us.

Thank you for choosing **CSK**.

This data sheet is for your information, a legally binding guarantee of the product's suitability for a peculiar application cannot be derived. No responsibilities can be undertaken for occurring damages. Our products are subject to a continuous production and quality control and leave our factory in perfect condition.

Replaces technical information dated 2011/06/26 Update: 2011/08/06